

High-Performance Fibre Lasers for Industrial Applications: Product Capabilities and Application Benefits

Michalis N. Zervas(*)
Optoelectronics Research Centre, University of Southampton
(*) also with SPI Lasers Ltd, Southampton, UK

Summary

High performance fibre lasers (FLs) are now well established as an extremely robust and reliable engine enabling a growing and diverse number of demanding industrial and medical applications. Compared to rival technologies, such as CO₂, LPSS, DPSS and disk lasers, FLs offer a number of unique characteristics that have resulted in their wide adoption in an increasing number of industrial sectors. In addition to enhancing and even replacing existing applications, FLs have been very successful in enabling and introducing novel applications and thus continuing to increase their market share.

Due to their robust and all-fibre, all-guided architecture, FLs are unique in offering instant turn-on operation without the need of regular tuning and re-alignment. The inherently large surface-to-volume ratio facilitates heat removal and minimizes the external cooling requirements. Also, there are no thermal lensing effects, which in turn results in excellent beam pointing stability. The beam quality can be engineered by proper fibre core design to match the application requirements. FLs are usually pumped by combining a number of extremely robust, telecommunication-grade, single-emitter broad-stripe multimode pump diodes. This results in laser systems with long lifetime, maintenance-free operation. In addition, due to very low loss, monolithic all-fibre geometries, they show record optical-to-optical, electrical-to-optical and overall wall-plug efficiencies. Finally, FLs show very small and compact footprint that facilitates their system integration.

Key to harnessing the benefits of an all-fibre laser configuration is the adopted pumping scheme. All SPI's laser products use a proprietary cladding-pumping technology (GTWave™) that enables multiport, multipoint pump injection and facilitates output power scalability. This modular approach results in robust, easily deployable CW/CWM fibre laser/amplifier systems with output power in the 10-400W ranges, covering the 1060nm and 1550nm wavelength regions. All active fibres are designed to be photodarkening free, adding into system reliability and longevity. SPI's high power FLs are used in a number of industrial and medical applications, including stent tube cutting, disc drive spot welding, electronic stencil cutting, automotive plastic welding, medical piece part welding, rapid prototyping etc.

When in a MOPA configuration, optical fibres, being extremely high gain media (>50dB small-signal gain per stage) can adequately compensate for their inherently reduced capacity to store energy and can provide high performance pulsed systems. SPI's redEnergy™ products exhibit pulsed operation with energies in the range of 0.8mJ and peak power in excess of 15kW, at 25kHz repetition rate. A unique feature of SPI's pulsed laser is the capability of producing high peak power pulses at very high rep rates (>400kHz). Such a laser has found widespread applications in a large number of demanding high-throughput marking applications.